

Psi	Feet	1/8		3/16		1/4		5/16		3/8		7/16		1/2		9/16		5/8	
		GPM	SS-X																
20	46					8.1	15	12.6	32	18.2	60	24.8	86	32.3	122	40.9	166	50.6	186
		%	SS			18%	12	27%	28	33%	50	33%	68	35%	93	33%	111	28%	119
			PELT				6		21		45		63		80				
30	69					9.9	50	15.5	111	22.3	162	30.4	247	39.6	296	50.2	338	62.0	372
						40%	49	49%	94	57%	157	56%	211	55%	269	43%	266	36%	280
							45		97		114		210		257				
40	92			6.4	44	11.4	106	17.9	186	25.8	286	35.1	392	45.8	495	57.9	442	71.6	604
				39%	42	55%	103	61%	181	64%	274	63%	365	60%	452	47%	447	39%	466
					37		96		173		251		353		434				
43	100			6.7	49	11.9	124	18.5	216	26.8	308	36.5	448	47.6	542	60.2	553	74.4	686
				39%	47	56%	119	64%	213	63%	303	65%	429	60%	512	47%	514	40%	539
					45		110		187		283		398		484				
50	115	3.2	14	7.2	71	12.7	164	19.9	280	28.8	398	39.2	556	51.1	680	64.7	688	80.0	846
		12%	8	47%	70	61%	160	64%	264	66%	393	66%	534	61%	650	48%	638	40%	668
					64		138		245		361		492		619				
52	120	3.26	16	7.3	75	13.0	176	20.3	299	29.3	416	39.9	593	52.1	702	65.9	733	81.5	891
		14%	10	47%	74	60%	169	65%	285	65%	414	63%	540	61%	687	48%	677	41%	713
					69		147		262		385		528		644				
60	139	3.51	27	7.9	102	14.0	219	21.9	364	31.6	509	43.0	711	56.0	863	70.9	880	87.7	1078
		21%	18	51%	100	62%	216	65%	357	64%	506	62%	662	60%	835	46%	812	40%	869
			16		91		183		340		490		655		798				
65	150	3.64	33	8.2	115	14.5	251	22.7	409	32.8	585	44.7	804	58.2	962	73.7	993	91.1	1188
		28%	28	51%	113	63%	245	66%	404	64%	569	62%	750	58%	910	46%	914	39%	962
			21		102		207		385		556		739		891				
70	162	3.79	41	8.5	132	15.1	282	23.6	470	34.1	655	46.4	888	60.5	1073	76.6	1103	94.7	1300
		33%	36	52%	130	62%	271	66%	455	65%	646	61%	829	57%	1005	44%	987	39%	1072
			26		119		232		420		618		812		987				
80	185	4.05	55	9.1	167	16.1	332	25.2	572	36.4	798	49.6	1067	64.7	1287	81.9	1306	101.2	1511
		36%	49	54%	165	60%	323	66%	558	63%	770	61%	1004	54%	1170	44%	1213	38%	1292
			37		145		285		515		725		987		1169				
90	208	4.3	69	9.7	202	17.1	391	26.8	660	38.7	945	52.7	1245	68.7	1485	86.9	1505	107.4	1681
		39%	62	55%	200	60%	382	65%	654	63%	914	60%	1179	53%	1357	44%	1420	36%	1454
			50		174		340		602		857		1128		1356				
100	231	4.52	82	10.2	240	18.0	458	28.2	786	40.7	1091	55.5	1434	72.3	1636	91.6	1673	113.2	1829
		41%	78	56%	237	60%	452	65%	761	63%	1067	58%	1346	51%	1539	42%	1596	35%	1627
			61		207		403		694		987		1279		1536				
110	254	4.75	101	10.7	273	18.9	534	29.6	875	42.7	1221	58.2	1576	75.9	1771	96.1	1783		
		45%	97	55%	270	59%	512	63%	849	62%	1207	56%	1502	49%	1690	30%	1722		
			72		235		451		776		1104		1407		1665				

SS-X: Stainless Steel Turgo w. large nozzle holder. SS: Stainless Steel Turgo w. 3/4" nozzle holder. Pelt: Harris Pelton. %: Efficiency of SS.